

# STANDARD AMS FEATURES

\* indicates feature is standard on particular shelter

## STEP 1: Pick Your Base Shelter

Choose the base shelter that will meet your requirements.

Listed below are features that come standard with each shelter.

STANDARD FEATURES	SAMS-58100	ESAMS-58203	HESAMS-58205
<b>DIMENSIONS &amp; WEIGHTS</b>			
Exterior Dimensions-stowed*	88"W X 108"L X 91.38"or 96.25"H	88"W X 108"L X 96.25"H	88"W X 108"L X 96.25"H
Interior Dimensions-stowed*	80.6"W X 100.6"L X 81.65"or X 86.5"H	80.91"W X 100.6"L X 86.5"H	68"W X 100.6"L X 86.5"H
Exterior Dimensions-deployed*	-	260"W X 108"L X 96.25"H	245.38"W X 108"L X 96.25"H
Interior Dimensions-deployed*	-	252.5"W X 100.6"L X 86.5"H	243"W X 95"L X 86.5"H
Floor Area-stowed*	56.5 sq.ft.	56.5 sq.ft.	48 sq.ft.
Floor Area-deployed*	-	170 sq.ft.	162 sq.ft.
Empty Weight	3,000 lbs.**	3,690 lbs.**	4,410 lbs.**
Gross Weight	10,000 lbs.	10,000 lbs.	10,000 lbs.
<b>TRANSPORTABILITY</b>			
Air Lift Certified (MIL-STD-913)	Certified-Max 12,000 lbs.	Certified-Max 12,000 lbs.	Certifiable-Max 12,000 lbs.
Helo External Air Transport (MIL-STD-913/209)	Certifiable-Max 10,000 lbs.	Certifiable-Max 10,000 lbs.	Certifiable-Max 12,000 lbs.
Transport by High Speed Mobility Wheel Set (not included)	•	•	•
Removable Detent Rails for Air Transport	•	•	•
Rail Transport	Max 11,000 lbs.	Max 11,000 lbs.	Max 11,000 lbs.
4-Way Forkliftable	•	•	•
Tie-Down Rings (installed in floor)	•	•	•
<b>ELECTRICAL</b>			
120/208VAC/3PH/60A/60Hz Power	•	•	•
60A Input Power Connector	•	•	•
50-ft. Shore Power Cable Mates w/Input	1	1	1
Ground Rod Kit	1	1	1

STANDARD FEATURES	LAMS-58201	ELAMS-58202	HELAMS-58204
<b>DIMENSIONS</b>			
Exterior Dimensions-stowed*	96"W X 178"L X 91.38"H	96"W X 178"L X 91.38"or 96.25"H	96"W X 178"L X 96.25"H
Interior Dimensions-stowed*	92.3"W X 174.3"L X 81"H	92.6"W X 174.3"L X 81"or 87"H	79.7"W X 174.3"L X 87"H
Exterior Dimensions-deployed*	-	266"W X 178"L X 91.38"or 96.25"H	258"W X 178"L X 96.25"H
Interior Dimensions-deployed*	-	263"W X 174.3"L X 81"or 87"H	256"W X 174.3"L X 87"H
Floor Area-stowed*	111 sq.ft.	112 sq.ft.	96 sq.ft.
Floor Area-deployed*	-	319 sq.ft.	310 sq.ft.
Empty Weight	3,990 lbs.**	3,840 lbs.** (91.4"); 4080 lbs. (96")	6,445 lbs.**
Gross Weight	15,000 lbs.	15,000 lbs.	15,000 lbs.
<b>TRANSPORTABILITY</b>			
Air Lift Certified (MIL-STD-913)	Certified-Max 15,000 lbs.	Certifiable-Max 15,000 lbs.	Certified-Max 15,000 lbs.
Helo External Air Transport (MIL-STD-913/209)	Certifiable-Max 13,240 lbs.	Certified-Max 13,240 lbs.	Certifiable-Max 13,240 lbs.
Transport by High Speed Mobility Wheel Set (not included)	•	•	•
Removable Detent Rails for Air Transport	•	•	•
Rail Transport	Max 11,000 lbs.	Max 11,000 lbs.	Max 11,000 lbs.
2-Way Forkliftable	•	•	•
Tie-Down Rings (installed in floor)	•	•	•
<b>ELECTRICAL</b>			
120/208VAC/3PH/60A/60Hz Power	•	•	•
60A Input Power Connector	•	•	•
50-ft. Shore Power Cable Mates w/Input	1	1	1
Ground Rod Kit	1	1	1

\*All dimensions are without generators; \*\*All tare weights are without ECUs or generators;

