


Expandable Internal Airlift/ Helicopter Slingable Container Unit (ISU®)



EISU shown with one personnel door and in stowed position and ready for shipment

The EISU is a 3-in-1 expandable version of the ISU® 90 Container. It occupies one pallet position (88" X 108") when stowed. When fully expanded, it offers 159 square feet of enclosed workspace. The wing walls of the closed container fold down to serve as floors in the deployed mode. The side "rooms" are enclosed within durable fabric walls and ceiling, which are supported by simple struts. Using two personnel, the container can be deployed in less than 15 minutes.

FEATURES

- Designed for internal air transport and helicopter sling lift
- Integral 463L air cargo pallet base - loads directly into aircraft cargo restraint system, as do all of AAR's ISU® containers
- Four-way forkliftable
- Two electrical shore-power hook up and interior 4-gang 120V receptacles
- Non-insulated fabric walls
- Two scissor-jacks on each side for wing-wall support

APPLICATIONS

- Parts Storage and Distribution, ASLs
- Temporary Warehouses
- Maintenance and Repair Functions
- Mobile Space for Administrative, Security, and Communications Functions
- Ablution Units
- Kitchens

PART #	INCLUDES	COLOR	GSA	DLA
56140-000	Two Soft Canvas Doors & Center Divider	GREEN	•	
56240-000		TAN	•	
56141-000	Two Soft Canvas Doors & One Personnel Door	GREEN	•	
56241-000		TAN	•	
56142-000	Two Soft Canvas Doors & Two Personnel Doors	GREEN	•	
56242-000		TAN	•	
56241-714	EISU 90EO 1 Door w/Kit 714 - Hot Dog Stand NSN: 8145-01-525-1991	TAN	•	•

DIMENSIONS

EXTERIOR STOWED	88"W X 108"L X 91.47"H
EXTERIOR DEPLOYED	245.20"W X 108"L X 91.47"H
INTERIOR STOWED	399 cu.ft.
INTERIOR DEPLOYED	Ceiling Height: min. 72.5", max 85", Floor: 159 sq.ft.

P/N	TARE WEIGHT	PAYLOAD	MAXIMUM GROSS WEIGHT
56X40	2,500 lbs.	7,500 lbs.	10,000 lbs.
56X41	2,500 lbs.	7,500 lbs.	10,000 lbs.
56X42	2,500 lbs.	7,500 lbs.	10,000 lbs.
56241-714	2,500 lbs.	7,500 lbs.	10,000 lbs.



EISU shown with two soft canvas doors in deployed position



EISU 90EO 1-Door shown deployed with Kit 714 (Hot Dog Stand)