


ISU® 90 LAUNDRY UNIT

Internal Airlift/ Helicopter Slingable
Container Unit (ISU®)



P/N	NSN	COLOR	GSA	DLA
56102-497	8145-01-472-7758	GREEN	•	•
56202-497		TAN	•	
DIMENSIONS				
EXTERIOR	108"W X 88"L X 91.35"H			
INTERIOR	399 cu.ft.			
WEIGHT	PAYLOAD CAPACITY	MAXIMUM GROSS WEIGHT		
3,200 lbs.	6,800 lbs.	10,000 lbs.		



Self-contained ISU® 90 Laundry Unit shown with optional High Speed Mobility Wheel Set (P/N 60340-002)

FEATURES

- Four doors, two on each 108" side
- 208 VAC three phase electrical power unit
- 53 load capability or 1,034 lbs. in 24 hours
- 65 gallon electric water heater
- Auto shut off switch for low water in water heater
- Dryer vents and hose with screens to filter water sediment and prevent rodent intrusion
- Power cable
- Fluorescent lighting (one on each side)
- Foot valve for pond or stream water pickup
- Self-priming pump for use with a water bladder or used to increase the water pressure in the system
- Awning cover for each side when doors are opened

PERFORMANCE STANDARD

- Completely intermodal
- Certifiable for helicopter external lift
- Four-way forklift compatible with 10,000 lb. fork trucks (72" tines)
- Military and commercial airlift compatible
- Lightweight and durable
- Double doors open on both 108" sides
- Winching rings provided
- Four unitized washers/dryers are installed in an ISU® 90 four-door container

WASHER/DRYER SPECIFICATIONS

- 19.4 lb. per cycle maximum load
- Washer features three cycles, three wash/rinse temperatures, and three water levels
- Dryer has automatic dry control with four cycles - automatic regular, automatic permanent press, timed dry, and air fluff
- 36-minute cycle time for cotton, 29-minute cycle time for permanent press and knits (times vary with outside temperature and humidity)

REQUIREMENTS

- Includes 208 VAC three phase electrical
- Water services require 2" hose with cam coupler (not included)
- 2" drain with no hub connector
- Minimum generator set 30kW connection for optimal sewage ejection system

ISU® 90 LAUNDRY UNIT